



KENCRO

CHEMICALS

SPECIFICATIONS: SULPHURIC ACID

APPEARANCE

Electrolytic grade acid is a clear, oily liquid having a sharp, penetrating odour.

SPECIFICATION DETAILS

Strength (% H ₂ SO ₄)	93.00 min.
Sulfur Dioxide (ppm SO ₂)	40 max.
Iron (ppm Fe)	200 max.
Chlorides (ppm Cl)	50 max.
Arsenic (ppm As)	3 max.
Selenium (ppm S)	20 max.
Lead (ppm Pb)	5 max.
Heavy Metals (ppm as Pb)	20 max.

SAFETY

As with any chemical, Sulphuric Acid requires care in handling. It is suggested that anyone involved with the procurement or handling of this chemical be familiar with the appropriate safety and handling precautions. Such information is available on the appropriate material and safety data sheet.

***FOR FIRE, HEALTH, SAFETY, AND FIRST AID INFORMATION, PLEASE REFER TO MSDS
All statements, information, and data presented are believed to be accurate and reliable but
are presented without guarantee, warranty, or responsibility***

Note: The quality of Electrolytic grade 1.835 is more carefully controlled than commercial grade, especially with respect to metallic contaminants. This product meets or exceeds Canadian Spec. 15-GP-8M (Apr.1983) and United States Spec. O-S-801-E (Nov. 1990).
All quantities are reported on a wt./wt. Basis.
This sales specification supersedes any previously issued specification unless clearly identified in the sales contract.

SPEC#: DSO0A8
file:spec/saspec.msdl/allfiles